

Bridge Rectifier

B125C1500G

125V / 1,5A

DATASHEET

from

www.web-bcs.com

OEM – General Semiconductor


Source: General Semiconductor Databook 1998

B40C1500G THRU B380C1500G

GLASS PASSIVATED SINGLE-PHASE BRIDGE RECTIFIER

Reverse Voltage - 65 to 600 Volts Forward Current - 1.5 Amperes


Case Style WOG



Dimensions in inches and (millimeters)

FEATURES

- ◆ Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- ◆ Glass passivated chip junctions
- ◆ High case dielectric strength
- ◆ Typical I_R less than $0.1\mu A$
- ◆ High surge current capability
- ◆ Ideal for printed circuit boards
- ◆ High temperature soldering guaranteed:
260°C/10 seconds, 0.375" (9.5mm) lead length,
5 lbs. (2.3kg) tension



MECHANICAL DATA

Case: Molded plastic body over passivated junctions

Terminals: Plated leads solderable per MIL-STD-750, Method 2026

Mounting Position: Any

Weight: 0.04 ounce, 1.1 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

	SYMBOLS	B40 C1500G	B80 C1500G	B125 C1500G	B250 C1500G	B380 C1500G	UNITS	
Maximum repetitive peak reverse voltage	VRRM	65	125	200	400	600	Volts	
Maximum RMS input voltage R + C-load	VRMS	40	80	125	250	380	Volts	
Maximum DC blocking voltage	VDC	65	125	200	400	600	Volts	
Maximum peak working voltage	VRWM	90	180	300	600	800	Volts	
Maximum non-repetitive peak voltage	VRSM	100	200	350	650	1000	Volts	
Maximum repetitive peak forward surge current	IFRM	10.0						Amps
Maximum average forward output current for free air operation at $T_A=45^\circ C$ R + L-load C-load	$I_{(AV)}$	1.6 1.5						Amps
Peak forward surge current single sine wave on rated load at $T_J=125^\circ C$	IFSM	50.0						Amps
Rating for fusing at $T_J=125^\circ C$ ($t < 100ms$)	IFt	12.5						A'sec
Min. series resistor C-load at $V_{RMS} = \pm 10\%$	Rt	1.0	2.0	4.0	8.0	12.0	Ohms	
Maximum load capacitance +50% -10%	CL	5000	2500	1000	500	200	μF	
Maximum instantaneous forward voltage drop per leg at 1.5A	Vf	1.0						Volts
Maximum reverse current at rated repetitive peak voltage per leg $T_A=25^\circ C$	I_R	10.0						μA
Typical thermal resistance per leg (NOTE 1)	$R_{\theta JA}$ $R_{\theta JL}$	36.0 11.0						$^\circ C/W$
Operating junction temperature range	T_J	-40 to +125						$^\circ C$
Storage temperature range	T_{STG}	-40 to +150						$^\circ C$

NOTES:

1. Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. at 0.375" (9.5mm) lead lengths with 0.2 x 0.2"

RATINGS AND CHARACTERISTICS CURVES B40C1500G THRU B380C1500G

