

Silicon Diode

GI1102

100V / 2,5A

DATASHEET

from

www.web-bcs.com

OEM – General Semiconductor


Source: General Semiconductor Databook 1998

GI1101 THRU GI1104

GLASS PASSIVATED FAST EFFICIENT RECTIFIER

Reverse Voltage - 50 to 200 Volts Forward Current - 2.5 Amperes

PATENTED*



Dimensions in inches and (millimeters)

* Brazed lead assembly is covered by Patent No. 3,930,306

FEATURES

- ◆ High temperature metallurgically bonded construction
- ◆ Glass passivated cavity-free junction
- ◆ Superfast recovery time for high efficiency
- ◆ Low forward voltage, high current capability
- ◆ Capable of meeting environmental standards of MIL-S-19500
- ◆ Hermetically sealed package
- ◆ Low Leakage
- ◆ High surge capability
- ◆ High temperature soldering guaranteed:
350°C/10 seconds, 0.375" (9.5mm) lead length,
5 lbs. (2.3kg) tension

MECHANICAL DATA

Case: JEDEC DO-204AP solid glass body
Terminals: Plated axial leads, solderable per MIL-STD 750, Method 2026
Polarity: Color band denotes cathode end
Mounting Position: Any
Weight: 0.02 ounce, 0.56 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

	SYMBOLS	GI1101	GI1102	GI1103	GI1104	UNITS
Maximum repetitive peak reverse voltage	VRRM	50	100	150	200	Volts
Maximum RMS voltage	VRMS	35	70	105	140	Volts
Maximum DC blocking voltage	VDC	50	100	150	200	Volts
Maximum average forward rectified current 0.375" (9.5mm) lead length (SEE FIG. 1)	IAV	2.5			2.0	Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method) at rated TL	IFSM	50.0				Amps
Maximum instantaneous forward voltage at 2.0A	VF	0.975			1.25 (NOTE 5)	Volts
Maximum DC reverse current at rated DC blocking voltage	IR	TA=25°C 2.0 TA=100°C 50.0		10.0 200.0		µA
Maximum reverse recovery time (NOTE 1)	trr	25.0			50.0	ns
Typical junction capacitance (NOTE 2)	CJ	45.0				pF
Typical thermal resistance (NOTE 1) (NOTE 4)	REJA REJL	65.0 20.0				°C/W
Operating junction and storage temperature range	TJ, TSTG	-65 to +175			-65 to +150	°C

NOTES:

- (1) Reverse recovery test conditions: IF=0.5A, IR=1.0A, IRT=0.25A
- (2) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts
- (3) Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length and mounted on P.C.B. with 0.5 x 0.5" (12 x 12mm) copper pads
- (4) Thermal resistance from junction to lead at 0.375" (9.5mm) lead length with both leads attached to heat sinks
- (5) Tested at IF=1.0A

RATINGS AND CHARACTERISTIC CURVES GI1101 THRU GI1104

