

Philips

Diode PBYL2520CTB

Datasheet

Schottky Dual Diode

PBYL2520CTB

20V / 25A


DATASHEET

OEM – Philips

Source: Philips Databook 1999

**Rectifier diodes
Schottky barrier**
PBYL2525CT, PBYL2525CTB series
FEATURES

- Low forward volt drop
- Fast switching
- Reverse surge capability
- High thermal cycling performance
- Low thermal resistance

SYMBOL**QUICK REFERENCE DATA**

$$V_R = 20 \text{ V} / 25 \text{ V}$$

$$I_{O(AV)} = 25 \text{ A}$$

$$V_F \leq 0.43 \text{ V}$$



GENERAL DESCRIPTION

Dual schottky rectifier diodes intended for use as output rectifiers in low voltage, high frequency switched mode power supplies.

The PBYL2525CT series is supplied in the SOT78 (TO220AB) conventional leaded package.
The PBYL2525CTB series is supplied in the SOT404 surface mounting package.

PINNING

PIN	DESCRIPTION
1	gate
2	drain ¹
3	source
tab	drain

SOT78 (TO220AB)**SOT404****LIMITING VALUES**

Limiting values in accordance with the Absolute Maximum System (IEC 134)

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{RRM}	Peak repetitive reverse voltage	PBYL25 PBYL25	-	20CT 20CTB	V
V_{RWM}	Working peak reverse voltage		-	20	V
V_R	Continuous reverse voltage	$T_{mb} \leq 120^\circ\text{C}$	-	20	V
$I_{O(AV)}$	Average rectified output current (both diodes conducting)	square wave; $\delta = 0.5$; $T_{mb} \leq 119^\circ\text{C}$	-	25	A
I_{FRM}	Repetitive peak forward current per diode	square wave; $\delta = 0.5$; $T_{mb} \leq 119^\circ\text{C}$	-	25	A
I_{FSM}	Non-repetitive peak forward current per diode	$t = 10 \text{ ms}$ $t = 8.3 \text{ ms}$ sinusoidal; $T_j = 125^\circ\text{C}$ prior to surge; with reapplied $V_{RRM(max)}$ pulse width and repetition rate limited by $T_{j,max}$	-	135 150	A
I_{RSM}	Peak repetitive reverse surge current per diode		-	1	A
T_j	Operating junction temperature		-	150	°C
T_{stg}	Storage temperature		-65	175	°C

1. It is not possible to make connection to pin 2 of the SOT404 package.

Rectifier diodes
Schottky barrier

PBYL2525CT, PBYL2525CTB series

THERMAL RESISTANCES

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th\ j-mb}$	Thermal resistance junction to mounting base	per diode both diodes	-	-	3	K/W
$R_{th\ j-a}$	Thermal resistance junction to ambient	SOT78 package, in free air SOT404 package, pcb mounted, minimum footprint, FR4 board	-	60 50	-	K/W

ELECTRICAL CHARACTERISTICS

All characteristics are per diode at $T_j = 25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_F	Forward voltage	$I_F = 12.5 \text{ A}; T_j = 150^\circ\text{C}$ $I_F = 12.5 \text{ A}; T_j = 125^\circ\text{C}$ $I_F = 25 \text{ A}; T_j = 125^\circ\text{C}$	- - -	0.36 0.38 0.5	0.43 0.47 0.62	V
I_R	Reverse current	$I_F = 25 \text{ A}$ $V_R = V_{RWM}$ $V_R = V_{RRM}; T_j = 100^\circ\text{C}$	-	0.54 1	0.66 5	mA
C_d	Junction capacitance	$V_R = 5 \text{ V}; f = 1 \text{ MHz}, T_j = 25^\circ\text{C} \text{ to } 125^\circ\text{C}$	-	600	-	pF

**Rectifier diodes
Schottky barrier**

PBYL2525CT, PBYL2525CTB series




Fig.1. Maximum forward dissipation $P_F = f(I_{F(AV)})$ per diode; square current waveform where
 $I_{F(AV)} = I_{F(RMS)} \times \sqrt{D}$.




Fig.4. Typical reverse leakage current per diode;
 $I_R = f(V_R)$; parameter T_J .




Fig.2. Maximum forward dissipation $P_F = f(I_{F(AV)})$ per diode; sinusoidal current waveform where a = form factor = $I_{F(RMS)} / I_{F(AV)}$.




Fig.5. Typical junction capacitance per diode;
 $C_d = f(V_R)$; $f = 1 MHz$; $T_J = 25^\circ C$ to $125^\circ C$.




Fig.3. Typical and maximum forward characteristic
 $I_F = f(V_F)$; parameter T_J .




Fig.6. Transient thermal impedance per diode;
 $Z_{th,j-mb} = f(t_p)$.